

CyberPower®

Model #: 1080

UPC: 649532010806

MSRP: \$31.99



The CyberPower 1080 surge suppressor is a Computer/Audio/Video Grade Surge Protector. This unit provides powerful surge suppression with a rating of 3600 Joules and has 10 outlets of MOV protection (4 transformer-friendly, 6 standard). It is equipped with a RJ-11 port that protects phone/fax/modem/DSL equipment, and also a RG-6 gold-plated coax port that is perfect for your cable modem, cable TV lines, and DSS equipment. EMI/RFI shielding will rid your equipment from any harmful interfaces, and MOV technology ensures the protection of all connected electronics, and the surge suppressor itself. CyberPower fully stands behind its products with a lifetime product warranty and Connected Equipment Guarantee of \$150,000.

- MOV (Metal Oxide Varistor) - MOV technology allows normal current to pass through the device, while diverting any surge/spikes through the ground circuit. This safely protects all connected electronics along with the surge suppressor itself.
- Transformer-spaced Outlets - Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- EMI/RFI Shielding - Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- ISO & Safety Certifications - All CyberPower's manufacturing facilities are ISO-9001 Quality Tested. Our products are also UL Listed and CSA Certified.
- Child-safe Outlets: Outlets on the surge suppressor that are not used can be "closed off" so unwanted objects cannot be electrically charged.
- Keyhole Mounting Slots – Convenient mounting slots are located on the back on the surge suppressor.
- Sturdy ABS Case – Constructed of impact-resistant composite material for maximum durability.

Technical Specifications

| | |
|---------------------------------------|--|
| General | |
| Model # | 1080 |
| Input | |
| Voltage | 110/120V Nominal |
| Plug Type | NEMA 5-15P |
| Plug Style | Right-angle |
| Cord Length | 8 ft |
| Output | |
| Outlets - Total | 10 |
| Outlets - Widely Spaced | 4 x NEMA 5-15R |
| Outlets - Normal Spaced | 6 x NEMA 5-15R |
| Surge Protection and Filtering | |
| Surge Suppression | 3600 Joules |
| Phone Protection (RJ11) | One-in/Two-out |
| Ethernet Protection (RJ45) | None |
| Coax Protection (RG6) | One-in/One-out |
| Maximum Surge Current | 180,000 Amps |
| Maximum Surge Current H-N | 120,000 Amps |
| Maximum Surge Current H-G | 30,000 Amps |
| Maximum Surge Current N-G | 30,000 Amps |
| Maximum Surge Voltage | 6,000V |
| Clamping Voltage | 330 V |
| Response Time | <1 ns |
| EMI/RFI Filtration | EMI/RFI 150KHz to 100MHz |
| Attenuation | Up to 58dB |
| Indicators | |
| Indicator Lights | Power (Red); Surge (Red); Ground (Green) |
| Physical | |
| Dimensions (WxHxD) | 11.75" x 4" x 1.75" |
| Weight | 2.2875 lbs. |
| Color | Bronze |
| Warranty | |
| Product Warranty | Lifetime |
| Connected Equipment Guarantee | Lifetime |
| CEG Amount | \$150,000 |